

SHERPAMATIC - GATE GUARDRAIL

STURDY AND COMFORTABLE PLATFORM

Sherpamatic gate is an exceptional work platform, delivering particularly impressive performances in even the most demanding work environments.

Safety comes first: This individual workstation complies with current French and European standards, and its gate guardrail automatically closes and locks when the user passes.

All-terrain comfort: Sherpamatic Braces is easy to transport thanks to its large ribbed wheels, and it offers a large, optimised workspace and perfect stability, even on challenging terrains.

A responsible product: Sherpamatic gate has been designed to respond to CSR challenges such as sustainability, recyclability, and reparability.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface
Material	Aluminium
Maximum load [kg]	150
Garantee [year]	5
Standard	EN 131-7 / PIRL NF P 93-353 / PIR NF P 93-352
Decree	2004-924
Recyclable up to [%]	86

All references comply with the EN 131-7 standard. The NF marking certifies the product's compliance with the NF P 93-353 standard (3-6-step models), the NF P 93-352 standard (7- and 8-step models), and the NF096 framework.



Gate guardrail with automatic closing

High comfort 600x400mm aluminium non-slip platform

2 interchangeable, removable tool-holding shelves

Lifting rings



Ribbed all-terrain wheels Ø175mm



- 4-sided rigid gate guardrail with automatic closing mechanism
- Two-way opening for the guardrail: open for the ascent, to be unlocked for the descent
- 80 mm non-slip steps
- Detachable compartmentalised tool holder, can hold up to 25 kg, with integrated hooks (max. 10 kg)
- XL tray supporting up to 25 kg
- Retractable stabilisers with millimetric adjustment system
- High comfort 600 x 400 mm non-slip aluminium platform with automatic











lock

- Anti-lift floor hook
- Comfortable, ergonomic workspace
- All-terrain Ø 175 mm moving wheels
- High safety covering footpads













NF certified product: Certifying body AFNOR Certification, 11, rue Francis de Pressensé, F-93571 La Plaine Saint-Denis Cedex (FR). Certification reference: Construction site equipment NF (NF096) available at www.marque-nf.com. A NF-certified individual mobile platform (or lightweight individual mobile platform) must be used with all the components listed in the model's nomenclature. All rights reserved. non-contractual images.

SHERPAMATIC - GATE GUARDRAIL

Reference		 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (m)	 (kg)	
02272913	3	2.11	0.35	0.7	2.7	1.29	0.68	1.54	22	3178740247607
02272914	4	2.37	0.35	0.94	2.94	1.49	0.68	1.62	23.4	3178740247614
02272915	5	2.62	0.35	1.18	3.18	1.68	0.68	1.66	25	3178740247621
02272916	6	2.87	0.35	1.41	3.41	1.87	0.68	1.83	26.4	3178740247638
02272917	7	3.12	0.35	1.64	3.64	2.05	0.68	2.01	28.6	3178740247645
02272918	8	3.37	0.35	1.87	3.87	2.24	0.68	2.2	30	3178740247133

The platform is counted as a step.

									
Number of rungs / steps	Folded product height (m)	Thickness of folded product (m)	Max. platform height (m)	Max. working height (m)	Base width (m)	Product width without stabilisers (m)	Overall width with stabilisers (m)	Weight (kg)	Barcode