## **SHERPASCOPIC - GATE GUARDRAIL**

## STURDY AND ALL-TERRAIN PLATFORM The Sherpascopic gate is an exceptional telescopic work platform, delivering particularly impressive performances in even the most demanding work environments. Safety

is a must: Sherpascopic gate meets the applicable French and European safety standards and its gate guardrail closes and locks automatically each time a user passes through it.

Work in comfort, always: Sherpascopic is easy to transport and features an intuitive height adjustive system, allowing it to quickly adapt to different worksite set-ups. A responsible product: Sherpascopic has been designed to respond to CSR challenges, such as sustainability, recyclability, and repairability, at every stage of its life span, from manufacturing to end-of-life.

Class	Professional
Use frequency	Ultra intensive
Use	Flat surface / Uneven surface
Material	Aluminium
Maximum load (kg)	150
Garantee (year)	5
Standard	EN 131-7 / PIRL NF P 93-353 / PIR NF P 93-352
Decree	2004-924
Decyclable up to (%)	88

## Recyclable up to (%) All models comply with the EN 131-7 standard.

The NF marking certifies the product's compliance with the NF P 93-353 standard (3–4-step models), the NF P 93-352 standard (5-7-step models and above), and the NFO96 framework







removable double

tool holder shelves

Gate guardrail with automatic closing aluminium non-slip





Guardrail deployment system Ribbed all-terrain wheels Ø175mm

- 4-sided rigid gate guardrail with automatic closing mechanism
- Telescopic surfaces allowing for level offsetting

600x400mm

platform

- Intuitive and secure height adjustment system, adjustment every 23cm
- Non-slip steps, 80 mm (fixed section) and 60 mm (telescopic section) •
- Detachable compartmentalised tool holder, can hold up to 25 kg, with • integrated hooks (max. 10 kg)
- XL tray supporting up to 25 kg
- High comfort 600 x 400 mm non-slip aluminium platform with automatic lock



Presented model: 02272961

- Ergonomic and comfortable workspace
- Retractable stabilisers with millimetric adjustment system
- All-terrain Ø 175 mm moving wheels
- High safety covering footpads







## **SHERPASCOPIC - GATE GUARDRAIL**

Reference	Ħ	<b>(</b> m)	<b>j</b> (m)	K (m)	κ /	<b>x</b> n) (m)	K (m)	(m)	(m)		<b>(</b> kg)	
02272960	3/4	2.16	0.4	1.99	0.72 0.1	95 <b>2.72</b>	2.95	1.64	0.68	1.69	26.4	3178740247683
02272961	5/7	2.62	0.4	2.64	1.14 1.	61 <b>3.14</b>	3.61	2.17	0.68	2.1	31.6	3178740247690
02272962	8/10	3.37	0.4	3.34	1.84 2	.3 3.84	4.3	2.74	0.68	2.66	35.8	3178740247706
02272963	8/11	3.37	0.4	3.57	1.84 2	.5 <b>3.84</b>	4.5	2.93	0.68	2.75	39.4	3178740247157
The platform is counted as a step.												
目	Ĭ	jį,	Ķ	Æ	Æ	Ķ	Ř	· <b>K</b> ·	Ц,	具	۵	
Number of rungs / steps	Folded product height (m)	Thickness of folded product (m)	Max. height of deployed product (m)	Min. platform height (m)	Max. platform height (m)	Min. working height (m)	Max. working height (m)	Base width (m	) Product width without stabili- sers (m)		Weight (kg	) Barcode

