🚔 ТИВЕЅСЛ-СОМЛВІ

INSULATED SHERPA - BRACES GUARDRAIL

THE COMFORT OF A SHERPA, WITH THE ADDED BONUS OF INSULATION

The insulated Sherpa is the leading fixed individual workstation on the market for the electrical trade. Safety first: This Sherpa meets the requirements of the applicable French and European standards, enabling users to work safely, offering them protection against low-voltage currents (<1,500 volts), and it features a semi-automatic rilsan-coated guardrail which is easy for users to set up. Comfortable working in any situation: The insulated Sherpa is easy to transport thanks to its large ribbed wheels, and it offers a large workspace. A responsible product: The insulated Sherpa is the result of an exacting designed process, taking challenges such as sustainability, recyclability, and CO2 impacts into consideration at every stage, from manufacturing to end-of-life.

Class	Professional
Use	Ultra intensive
Type of floor	Flat surface
Material	Glassfiber / Aluminium
Max load (kg)	150
Warranty (year)	2
Standard	EN 131-7 / PIRL NF P 93353 / EN50528
Decree	2004-924



fibreglass uprights







Covering non-slip footpads

Ribbed all-terrain wheels Ø175mm

Anti-lift floor hook Guardrails with braces and insulating rilsanised protection









Guardrail

- High comfort positioning system fibreglass uprights 600x400mm nonslip platform in eco- slip platform in ecosourced wood
 - High comfort 600x400mm nonsourced wood

XL 25 kg resistance tray

- MThe fibreglass material used for the uprights means users are • protected from electric shocks while working
- 4-sided rigid guardrail with braces and insulated rilsan-coated protection
- 80 mm non-slip steps
- Detachable compartmentalised tool holder, can hold up to 25 kg, with integrated hooks (10 kg)
- XL tray supporting up to 25 kg





Insulated sherpa braces guardrail 4 steps

- High comfort 600 x 400 mm non-slip floor in • ecologically sourced wood
- Ergonomic and comfortable workspace
- Retractable stabilisers with millimetric • adjustment system
- All-terrain Ø 175 mm moving wheels



INSULATED SHERPA - BRACES GUARDRAIL

Reference	Ħ	(m)	(m)	K j	n) (m)	(m)	(m)	(kg)	
02272853	3	2,12	0,34	0,71 2,	71 1,29	0,68	1,51	20,3	3178740248830
02272854	4	2,37	0,34	0,94 2,5	1,48	0,68	1,61	21,3	3178740248840
02272855	5	2,62	0,34	1,17 3,	1,67	0,68	1,6	22,8	3178740247188
The platform is cou	nted as a step.								
	6	r	π	Ť	-	н	н		
Ħ	Í	, ji ,	Æ	Ķ	,K.	L L		Å	

