

DOUBLE INSULATED LADDER

High-performance insulated unit

The Tubesca Comabi self-stable Double insulating ladder with fibreglass uprights provides access to a maximum height of 2.84 metres while complying with the EN 50528 and EN 57418/EN 131 standards and decree 96-333.



- Fibreglass uprights for protection against electric shocks up to 1, volts.
- Aluminium steps 8 mm wide for extra-light weight.
- Retaining strap.
- Standard EN 5528 defines values for protecting users against low voltage currents up to 1,5 volts. The flashover test is done at 1, volts.



Bucket hook



High-security covering footpads with wear indicator

Product characteristics

Use	Ultra intensive
Use	Flat floor
Max access / working height (m)	2,84
Material	FIBER GLASS
Maximum load (kg)	150
Warranty (years)	5
Norms	EN 131 , EN 50528
Decree	96333
NF Label //	

Ref.	Overall H	Nb of steps	Weight	Width stabilizers folded (m)	Wheelbase	Section	Max access Height (m)	Gencod
04255004	1,02	2x4	6	0,46	1	50	1,92	3178740020187
04255006	1,48	2x6	9	0,51	1,38	50	2,38	3178740020194
04255008	1,94	2x8	12	0,56	1,75	50	2,84	3178740020200