

MP PRO

The european reference for professionals



- : Anodised finish, very smooth for working clean-handed.
- : Platform reinforced in moulded epoxy-coated aluminium.
- : Patented anti-rotation system, rigid step/upright connections.
- : Flared base for increased stability.
- : Steps 90 mm wide.
- : 280 x 250 mm platform.



Aluminium hinge mounted on a polyamide element. No risk of seizure



Highly resistant connections to uprights



Covering footpads high security Ref. 9715



Screw tray with cover



Bucket hook Max. weight 1 kg



Maximum safety. The guardrail eliminates any risks of tipping over forward

Product characteristics	
Use	Ultra intensive
Use	Flat floor
Max access / working height (m)	3,98
Material	ANODISED ALUMINIUM
Maximum load (kg)	150
Warranty (years)	5
Norms	EN 131
Decree	96333
NF Label //	

Ref.	Folded H (m)	Platform height	Wheelbase	Nb of steps	Weight (kg)	Width (without stab)	Mini requirements EN131	Access / working Height (m)	Gencod
02370003	1,48	0,66	0,79	3	4,8	0,48	0,41	2,66	3178740001681
02370004	1,73	0,88	95	4	6,4	0,52	0,44	2,88	3178740001421
02370005	1,97	1,1	1,1	5	7,5	0,57	0,46	3,1	3178740001063
02370006	2,21	1,32	1,25	6	8,7	0,61	0,49	3,32	3178740004583
02370007	2,46	1,54	1,41	7	10,3	0,66	0,51	3,54	3178740002015
02370008	2,7	1,76	1,56	8	11,6	0,7	0,54	3,76	3178740000400
02370009	2,94	1,98	1,71	9	13,4	0,74	0,56	3,98	3178740002794