

# PLATINIUM 2-SECTION PUSH-UP

The ladder for medium level work



- : Lightweight and easy to set up.
- : Interlocking clips secure the sliding section for safe use.
- : Very simple to erect for reaching medium levels without losing any time.
- : These models are often used with hooks on the upper section (see table below).
- : Reinforced upright profiles with 3 x 3 mm rungs.




Wide base for increased stability



Ribbed end-piece for increased stability



Models with hooks



Optional retaining bar (ref. 9612) for models with hooks



Product characteristics	
<b>Use</b>	Ultra intensive
<b>Use</b>	Flat floor
<b>Max access / working height (m)</b>	10,9
<b>Material</b>	Aluminium
<b>Maximum load (kg)</b>	150
<b>Warranty (years)</b>	5
<b>Norms</b>	EN 131
<b>Decree</b>	96333
<b>NF Label //</b>	

Ref.	Folded H (m)	Deployed Height (m)	Nb of steps	Weight	Width stabilizers deployed (m)	Section	Max access Height (m)	Gencod
02422812	3,54	6,11	2x12	14,3	1,01	79,5	7,01	3178740162382
02422814	4,1	6,95	2x14	16,4	1,11	79,5	7,85	3178740162399
02422816	4,67	8,35	2x16	21,7	1,21	90	9,25	3178740162405
02422818	5,23	9,19	2x18	23,9	1,21	90	10,9	3178740162412
02422806	1,79	2,94	2x6	6,8	0,71	66	3,84	3178740169169
02422807	2,07	3,5	2x7	7,7	0,71	66	4,4	3178740162351
02422808	2,35	4,06	2x8	8,7	0,81	66	4,96	3178740162368
02422810	2,91	4,9	2x10	10,5	0,91	66	5,8	3178740162375