

KOLOS

The extra comfortable stepladder

With its 110 mm wide steps, cast aluminium hinges and reinforced uprights, KOLOS really stands out for its toughness and comfort. It complies with the EN 131 standard and decree 96333 and has the NF quality label.




5-step model

- ▶ Crimped, non-slip steps in extruded aluminium, 110 mm wide
- ▶ One-piece hinges in ribbed, ultra-resistant cast aluminium
- ▶ Tool-holder with integrated closing
- ▶ Platform 280 x 250 mm
- ▶ Footpads full-covering, non-slip pads with wear indicator
- ▶ Epoxy-painted uprights with high-resistance step fittings


Product characteristics

Use	Intensive
Type of floor	Flat floor
Max work / access height (m)	3,82
Material	PAINTED ALUMINIUM
Maximum load (kg)	150
Warranty (years)	5
Standard	EN 131
Decree	96 333


NF Label //



Non-slip steps in extruded aluminium, 110 mm wide



One-piece hinges in ribbed, ultra-resistant cast aluminium



High resistant uprights



Straps for 7/8-step models



Optional ramp (ref: 02376450)



Tool-holder with integrated closing



High-security covering footpads



Epoxy-painted uprights

Ref.	Folded H (m)	Platform H	Wheelbase (m)	Nb of rungs/steps	Weight (kg)	W. (without stab)	Access / work H (m)	EAN barcode
02375813	1,44	0,66	0,75	3	4,8	0,43	2,66	3178740203016
02375814	1,69	0,89	0,91	4	5,8	0,46	2,89	3178740203023
02375815	1,94	1,12	1,06	5	6,8	0,48	3,12	3178740203030
02375816	2,19	1,36	1,22	6	7,8	0,51	3,36	3178740203047
02375817	2,44	1,59	1,37	7	9	0,54	3,59	3178740203054
02375818	2,68	1,82	1,52	8	10,1	0,56	3,82	3178740203061