


SPEEDY 3 EXPORT


THE FOLDING EXTENDABLE UNIT



- Speedy 3 can be erected extremely quickly without any screws or tooling
- Its width enables it to go through doorways 0.73 m wide without being completely disassembled
- The folding base provides a high level of rigidity much appreciated by users. It can be opened in a single movement
- Platform is wide and comfortable. It is equipped with added wooden toe boards for guaranteed safety
- The ladders are connected together by pins to be put in place during assembly.



The ladders are interconnected by pins fitted during assembly



Toe boards are slotted in position for easy fitting



The wheels are fitted with powerful brakes that contributes to holding the unit perfectly stable when in working position



The ends of the horizontal tubes and diagonals have toothed jaws that automatically position themselves around the rungs. A highly dependable system

Product characteristics

Use	Moderate
Use	Flat floor
Max access / working height (m)	7,2
Material	Aluminium
Maximum load (kg / m²)	200
Warranty (years)	3
Norms	EN 1004

Ref.	DIMENSIONS								Number of plat-forms
PACK1	1.80	0.90	26.5	1.75	0.83	-	-	2.90	1
PACK1+2	2.90	1.70	36.5	1.75	0.83	-	-	3.70	1
PACK1+2+3	4.60	3.40	66.0	1.75	0.83	3.90	3.40	5.40	1
PACK1+2+3+4	6.30	5.20	87.5	1.75	0.83	3.90	3.40	7.20	2

Ref. Pack	Designation		SPEEDY 3 PACKS - COMPOSITION								
			Stabilizer	Folding base with ladder 1x6	Cross-brace/brace	7-rung ladder	4-rung ladder	Platform	Diagonal	Set of 4 toe boards	
02408321	PACK1	26.5	0	1	0	0	0	1	1	0	3178740182380
02408322	PACK2	10.5	0	0	3	0	2	0	0	0	3178740180397
02408323	PACK3	29.5	4	0	2	2	0	0	2	1	3178740180403
02408324	PACK4	21.5	0	0	2	2	0	1	4	0	3178740078410