

ISOLEX 2-SECTION ROPE-OPERATED LADDER

The lightweight insulated ladder

The ISOLEX double aluminium and fibreglass extension ladder provides access to a height of 11.72 metres. Its aluminium content and extension wheels guarantee safety and lightness. It complies with the EN 131, EN 50528 and EN 61478 standards and decree 96-333. It has the NF quality labels.



- ▶ Very lightweight ladder with fibreglass/aluminium uprights.
- ▶ Reinforced uprights.
- ▶ UV-protected rope, guaranteed against ageing.
- ▶ 30 x 30 mm rungs.

Product characteristics	
Use	Highly intensive
Type of floor	Flat floor
Max access / working height (m)	10.88
Material	Fibreglass
Maximum load (kg)	150
Warranty (years)	5
Standard	EN 131, EN 50528
Decree	96333
NF Label //	



Wide base for increased stability



Sliding section locking system



Guide wheels Ø 1 mm



Locking pivot with automatic return

Delivered in plastic film.

Ref.	Folded H (m)	Deployed H (m)	Nb of rungs/steps	Weight (kg)	W. stabilizers deployed (m)	W. (without stab)	Section	Max access / work H (m)	EAN barcode
04432312	3.53	5.77	2x12	19.5	1.01	0.43	90	6.67	3178740186623
04432314	4.1	6.9	2x14	28	1.11	0.43	90	7.8	3178740186630
04432316	4.66	8.02	2x16	32	1.21	0.43	90	8.92	3178740186647
04432318	5.22	9.14	2x18	36.5	1.21	0.43	90	10.04	3178740186654
04432320	5.78	9.98	2x20	39.5	1.21	0.43	90	10.88	3178740186661