

PRONOR 2-SECTION ROPE-OPERATED

The essential professional unit for medium levels

The Pronor rope-operated aluminium extension ladder has 2 sections and reaches up to 12.55 metres. Its slot-in pads, 30 x 30 mm rungs and cast aluminium pivot lock guarantee reliability and strength in all environments. It complies with the EN 131 standard and decree 96-333. It has the NF, GS and VGS quality labels.



- Runners in polyamide for easy-sliding sections.
- Locking pivot in high-resistance cast aluminium.
- Very easy to handle and erect.



Locking pivot in cast aluminium. Safe and accurate use



Distance between rungs 28 mm



Guide wheels Ø 1 mm



Ribbed non-slip footpads



For working alongside walls



Additional side stabilizers

Product characteristics

Use	Intensive
Use	Flat floor
Max access / working height (m)	12,55
Material	Aluminium
Maximum load (kg)	150
Warranty (years)	5
Norms	EN 131
Decree	96333
NF Label //	

Ref.	Folded H (m)	Deployed Height (m)	Nb of steps	Weight	Width stabilizers deployed (m)	Section	Max access Height (m)	Gencod
01232112	3,52	6,04	2x12	18,5	1,23	79	6,94	3178740186418
01232113	3,8	6,6	2x13	19,5	1,23	79	7,51	3178740186425
01232115	4,37	7,45	2x15	21,8	1,23	79	8,36	3178740186432
01232116	4,65	8,01	2x16	22,6	1,23	79	8,91	3178740186449
01232118	5,21	9,13	2x18	26,7	1,23	90	10,04	3178740186456
01232120	5,77	9,97	2x20	29,2	1,23	90	10,88	3178740186463
01232123	6,61	11,65	2x23	35,5	1,23	101	12,55	3178740186470