

2-SECTION ROPE-OPERATED INSULATED LADDER


High-level work with electrical insulation




- Fiberglass/polyester uprights to protect the user against electric shock.
- Locking pivot with automatic return system.
- Very lightweight product with aluminium rungs.



Wide base for increased stability



Guide wheels



Locking pivot with automatic set up system



UV-protected rope for resisting against the sun and bad weather



Optional cradle for use on posts Ref. 9224

Product characteristics

Use	Ultra intensive
Use	Flat floor
Max access / working height (m)	10,1
Material	FIBER GLASS
Maximum load (kg)	150
Warranty (years)	3
Norms	EN 131 , EN 50528
Decree	96333
NF Label //	

Ref.	Folded H (m)	Deployed Height (m)	Nb of steps	Weight	Width stabilizers folded (m)	Width stabilizers deployed (m)	Section	Max access Height (m)	Gencod
04332312	3,63	6,14	2x12	21	0,43	1,01	66	7,04	3178740186517
04332314	4,16	7,24	2x14	29	0,43	1,11	90	8,14	3178740186524
04332316	4,72	8,36	2x16	32,5	0,43	1,81	90	9,26	3178740186531
04332318	5,28	9,2	2x18	35,5	0,43	1,81	90	10,1	3178740186548